

FINISHING TOUCHES LINEATE 2 GP600

SPECIFICATIONS

Style.....Lineate 2 GP600
ConstructionTPR Rubber Wall Base
Thickness25"
Size6" (152.4mm)
Packaging48' linear feet per carton (14.63m), 8 lengths per carton
Length6' (1.83m) length only

TESTING

Construction (ASTM F1861)Standard for Rubber Wall Base Type TP
Dimensional Stability (ASTM F1861-01)..Meets standard for wall base; no more than -0.007" (0.6%)
Flame Spread (ASTM E84-91A).....50 (Class B), Smoke Density <450

SUSTAINABILITY

Recycled Content10% pre-consumer
DOP Free.....Phthalate Free
DEHP Free.....On the STATE OF CALIFORNIA list of chemicals "known to cause cancer or reproductive toxicity"
LEEDMay contribute to LEED credits
MR 5.1 NC/CI Regional Materials: 20% manufactured regionally (Dalton, GA 30722)
MR 5.2 CI Regional Materials: 10% extracted regionally
MR 4.2 Recycled Content: 10% pre-consumer

MADE IN USA

WARRANTY

Limited 1 Year Commercial Rubber Wall Base Warranty

For samples or other technical information, please contact your sales representative or call Signature at 800-809-7086.

