

FINISHING TOUCHES UNDERSCORE UN425

SPECIFICATIONS

Style..... Underscore UN425
ConstructionTPR Rubber Wall Base
Thickness125”
Size4.25” (107.95mm)
Packaging120’ linear feet per carton (36.576m)
Roll.....120’ (36.576m) continuous rolls only

TESTING

Construction (ASTM F1861)Standard for Rubber Wall Base Type TP
Dimensional Stability (ASTM F1861-01). .Meets standard for wall base; no more than -0.007” (0.6%)
Flame Spread (ASTM E84-91A).....50 (Class B), Smoke Density <450

SUSTAINABILITY

Recycled Content10% pre-consumer
DOP FreePhthalate Free
DEHP Free.....On the STATE OF CALIFORNIA list of chemicals “known to cause cancer or reproductive toxicity”
LEEDMay contribute to LEED credits
MR 5.1 NC/CI Regional Materials: 20% manufactured regionally (Dalton, GA 30722)
MR 5.2 CI Regional Materials: 10% extracted regionally
MR 4.2 Recycled Content: 10% pre-consumer

MADE IN USA

WARRANTY

Limited 1 Year Commercial Rubber Wall Base Warranty

For samples or other technical information, please contact your sales representative or call Signature at 800-809-7086.

